

STRIKER
CRUSHING & SCREENING



STRIKER JM1310

Jaw Crusher



Unlimited Solutions
for Limited Resources

MINING RANGE

Tracked Jaw Crushers



Tracked Plant Features

Vibrating Grizzly Feeder

Feeding the materials into the Jaw Crusher and/or fines chute is a vibrating grizzly feeder including :

Vibrating Unit

Twin shaft exciter unit mounted under the rear of the vibrating feeder. The exciter is driven by a single hydraulic motor and produces a forward linear motion.

Pan

The feeder floor is fitted with Hardox 400 bolted replaceable wear liners. These extend the quality and life of the feeder.

Grizzly Section

The grizzly section is a double step grizzly that is easily removed.

Feed Hopper

The feed hopper is manufactured from Mild Steel and is fitted with bolt in Hardox 400 liners. To raise and lower the wings, hydraulic cylinders are used to bring the travelling height down to a minimum and allow for maintenance to the vibrating feeder.

Track Frame

Manufactured from heavy-duty frame steel with 4.2m longitudinal centres along with 500 wide tracks as standard with an overall track width of 3.5m.

Forward Product Conveyor

The forward product conveyor or main conveyor is a 1500mm wide, troughed belt conveyor with a fixed tail section and a discharge height of 3.6m high. The belt is driven via dual hydraulic drive motors.

Side Discharge Conveyor

The side discharge dirt conveyor is hydraulic folding, 600mm wide giving a discharge height of approximately 2.4m to the top of the head drum. The belt is driven via a hydraulic drive motor (optional).

Fines Transfer Chute

Fitted beneath the vibrating grizzly is the fines transfer chute. This chute transfers the material passing the grizzly bar setting onto either the forward product conveyor or the side discharge conveyor.

Magnet

A magnetic cross-belt separator is suspended over the on-plant product conveyor and is complete with permanent magnet and a hydraulic drive (optional).

Powerpack

CATERPILLAR model C13 engine with electronic governing and emission control powers the plant. Rated at 425 bHP @ 1800 to 2000 rpm designed to drive the jaw via a KPTO transmission.

Jaw Crusher

The Jaw Crusher provides the latest technology in Heavy Duty Crusher design that delivers high production, large feed opening, bolted mainframe and a cast swing jaw holder. The crusher is designed to handle hard rock, ores and demolition concrete for the quarrying and mining industries. Designed to compliment Track installations, these rugged machines are manufactured with heavy-duty parts for optimum operation and long life.

Extra Heavy Duty Body


The Jaw Crusher body is a four piece, fully bolted and doweled heavy duty structure. Both the front and rear frames are cast high strength steel with side plates produced from high strength structural plate.

Crushing Chamber

The jaws are a corrugated manganese jaw which are reversible, top to bottom. The swing jaw is a fully enclosed section of cast steel construction. Both the fixed and moving jaws are retained with a wedge locking system.

Options

Special features are available depending on the client's requirements. A conveyor weigh scale can be fitted along with extended hopper wings for an improved size in feeding area. Engine fire suppression, dust suppression, optimax feed controller.



MODEL	A	B	C	D	E	F	G	H	K	L	J	TRANSPORT			
												WIDTH	HEIGHT	LENGTH	WEIGHT
JM1310	17000	3200	4100	4650	4650	5300	3350	6350	5350	500	900	3500	4650	17300	97T

* - WEIGHT VARIABLE WITH OPTIONS

STRIKER AUSTRALIA Pty Ltd

Perth Office: 9 Egmont Road Henderson WA 6166, Australia Ph: +61 8 9437 3533 Fax: +61 8 9437 3544

Brisbane Office: 26 Leonard Crescent Brendale Queensland 4500, Australia Ph: +61 7 3881 1227 Fax: +61 7 3881 1996

STRIKER CRUSHING & SCREENING Sdn. Bhd.

Malaysia Office: Plot No. 44, PT8286, Jalan Johan 2/4, Estate Perindustrian Pengkalan 2, Fasa 2, 31550 Pusing, Batu Gajah, Perak. Ph: +605 366 8188 Fax: +605 365 2688

STRIKER ENGINEERING MACHINERY (SHENYANG) Co., Ltd.

China Office: Room 3010, Royal WanXin International Mansion, 110003 Shenyang, China. Ph: +86 (24) 2353 4388 Fax: +86 (24) 2353 4288

E-mail: info@strikercrushing.com Website: www.strikercrushing.com

All reasonable steps have been taken to ensure the accuracy of this publication. However, due to our policy of continual product development, Striker reserve the right to change details without prior notice. All machines supplied in accordance with our standard conditions. Illustrations and photos may show optional equipment.

